(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
19 September 2002 (19.09.2002)

PCT

(10) International Publication Number
WO 02/073237 A2

(51) International Patent Classification[7]: G01V 1/00

(21) International Application Number: PCT/US02/07451

(22) International Filing Date: 13 March 2002 (13.03.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/804,892   13 March 2001 (13.03.2001)   US

(71) Applicant: WESTERNGECO, L.L.C. [US/US]; 10001 Richmond Avenue, Houston, TX 77042 (US).

(72) Inventor: WISECUP, R., Daniel; 6611 South Walden Street, Aurora, CO 80016 (US).

(74) Agents: FIGATNER, David, S. et al.; WesternGeco, 10001 Richmond Avenue, Houston, TX 77042 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SEISMIC PROCESSING METHOD TO IMPROVE SPATIAL RESOLUTION

(57) Abstract: Temporal and/or spatial frequencies of spatially and digitally sampled 2-D or 3-D seismic data above the Nyquist frequency are preserved in full time migration of partial time migration (DMO) of 2-D and 3-D are preserved. Use is made of the fact that migration operators applied to input seismic data produce an output that need not correspond to prespecified temporal or spatial sampling values, and for sufficiently long migration operators, gives substantially uniform sampling at higher rates than the spatial and temporal Nyquist frequencies. Exact values of the partial migrated outputs are accumulated in an output buffer prior to combining them to give a migrated output with high temporal and/or spatial frequencies preserved.

WO 02/073237 A2

WO 02/073237 A2

SEISMIC PROCESSING METHOD TO IMPROVE SPATIAL RESOLUTION

This invention relates to the field of seismic data processing. More particularly, this invention relates to a method of obtaining improved spatial and/or temporal resolution of 2-D or 3-D seismic data.

A seismic survey represents an attempt to map the subsurface of the earth by

5　sending acoustic or elastic energy down into the ground and recording the "echoes" that return from the rock layers below. The source of the downgoing acoustic or elastic energy might come, for example, from explosions or seismic vibrators on land, and air guns in marine environments. During a seismic survey, the energy source is moved across the surface of the earth above a geologic structure of interest. Each

10　time the source is actuated, it generates a seismic signal that travels downward through the earth, is reflected and/or diffracted, and, upon its return, is recorded at a great many locations on the surface. Multiple source-actuation /recording combinations are then combined to create a near continuous profile of the subsurface that can extend for many kilometers. In a two-dimensional (2-D) seismic survey, the

15　source and recording locations are generally laid out along a single straight line, whereas in a three-dimensional (3-D) survey the source and recording locations are generally distributed across the surface in a grid pattern. In simplest terms, a 2- D seismic line can be thought of as giving a cross sectional picture (vertical slice) of the earth layers with reflector locations roughly midway between the source positions and

1

the receiver positions. A 3-D survey produces a data "cube" or volume that is, at least

conceptually, a 3-D picture of the subsurface that lies beneath the survey area with

reflector positions roughly midway between the source positions and the receiver

positions in the acquisition grid.

5   A seismic survey is composed of a very large number of individual seismic

recordings or traces. In a typical 2-D survey, there will usually be several tens of

thousands of traces, whereas in a 3-D survey the number of individual traces may run

into the multiple millions of traces. General background information pertaining to 3-

D data acquisition and processing may be found in Chapter 6, pages 384-427, of

10   Seismic Data Processing by *Ozdogan Yilmaz*, Society of Exploration Geophysicists,

1987, the disclosure of which is incorporated herein by reference.

       Unprocessed seismic data is only of limited use to an explorationist. Seismic

data as it is acquired in the field is seldom used directly, but instead it is first returned

to a processing center where various mathematical algorithms are applied to the

15   digital seismic data to enhance its signal content and generally make it more amenable

to interpretation. A key step in a typical seismic processing sequence is seismic

migration.

       As is well known to those skilled in the art, the dip, location and character of a

reflector on an unmigrated seismic section is rarely representative of the true dip,

20   subsurface location and character of the structural or stratigraphic feature that gave

rise to that reflector. Except in the case where the subsurface consists of

homogenous, horizontal layers, the recorded seismic expression of a structural or

stratigraphic event must be migrated before it can be reliably used to locate

subsurface features of interest. In areas of steep dip, a reflection that is apparently

located directly below a particular surface point before migration may, after

migration, actually be found several hundreds of meters away. Additionally, in

5   complex structural areas where faulting, severe asymmetrical folding and sharp

synclines are present, diffractions and multiple reflections may interfere with

reflections from the primary reflectors to the point where, without migration, the

resulting seismic section bears little or no resemblance to the actual subsurface

structure.

10   Broadly speaking, migration improves a seismic section or volume by

"focusing" the seismic data contained therein, a process that is conceptually similar to

that of "focusing" the image produced by a slide projector in order to obtain the

sharpest screen image. Migration improves the seismic image by correcting the

lateral mispositioning of dipping seismic reflectors; collapsing diffractions caused by

15   point scattering centers and subsurface fault terminations; resolving crossing

reflectors (conflicting dips); and improving the vertical and lateral resolution of the

seismic data, among many others. A general description of the many ways that

migration improves seismic data may be found in, for example, Chapters 4 and 5, and

Appendix C, pages 240-383, and 507- 518, of Seismic Data Processing by *Ozdogan*

20   *Yilmaz*, Society of Exploration Geophysicists, 1987, the disclosure of which is

incorporated herein by reference. As a general rule, seismic data that have been

properly migrated reveal an enhanced or a truer picture of the subsurface than

3

unmigrated seismic data, the ultimate goal of seismic migration being to produce a seismic section or volume that accurately represents the configuration and character of the geology of the subsurface.

United States Patent 6,049,759 to *Etgen* discloses a method of prestack

5   migration of 3-D seismic data. As taught therein, there are two broad variants of seismic migration: migration after stack (poststack) and migration before stack (prestack). Post- stack migration is applied, as the name suggests, to seismic traces after they have been stacked--a stacked seismic trace being one that is formed by combining together two or more traces after Normal-Moveout (NMO) correction to

10   form a single composite trace that is an approximation of a zero offset trace at that location. Prestack migration, on the other hand, is applied to seismic traces before they have been stacked. Other things being equal prestack migration is always preferred--both theoretically and in practice--because it has the potential to produce a more accurate picture of the subsurface stratigraphy and structure. However, the

15   computational effort involved in computing a prestack migration is many times that required to do a poststack migration. For 2-D seismic lines, this additional computational effort is generally manageable and, except for the longest lines, prestack migration is often applied to seismic data that has been taken in areas where the subsurface structure is complicated. Many 3-D data sets, on the other hand,

20   contain far too many traces to be cost-effectively migrated via conventional prestack algorithms.

An attractive algorithm to approximate full prestack migration in 3-D and

4

even for 2-D seismic acquisition is the use of Pre-stack Partial Migration, also known as Dip Moveout Correction (DMO). DMO moderates the effect of reflection-point smear and enables events to be stacked coherently moderating the effects of dip and/or azimuth. Thereafter the data can be stacked and post-stack migrated

5   conventionally but with a substantial degree of data compression. An additional advantage is that DMO is a relatively small correction that tends to be insensitive to errors in the estimated velocity used for NMO corrections. This is a significant improvement over NMO-stack.

There are various alternative equivalent implementations of DMO. Perhaps

10   the most popular are Hale's method and the summation method of Deregowski and Rocca. Hale's Fourier-based method, proposed in his doctoral thesis "Dip Moveout by Fourier Transform" submitted to Stanford University Geophysics Department, May 1983, is carried out in frequency/wave vector (f,k) domain. Deregowski and Rocca's summation method described in "Geometrical Optics and Wave Theory of Constant

15   Offset Sections in Layered Media," Geophysical Prospecting 29, 374-406 (1981), is carried out in time/space (t,x) domain. It involves summation of data along a "DMO trajectory."

The migration and DMO methods disclosed in prior art and mentioned above start with digitally sampled data from a single seismic line or 2-D grid of seismic lines

20   and obtain an output at locations that correspond to nominal positions of locations midway between the seismic sources and detectors used in the acquisition process. All of the time domain migration and DMO methods involve summation of data

moved from a recorded position to an output position. In principle this is similar to

what is performed in NMO correction of the data in a line of seismic data.

United States Patent 5,596,546 to *Wisecup* teaches a method of preserving

temporal frequency components in NMO corrected stack data that are normally lost in

5   conventional NMO processing. *Wisecup* teaches the NMO correction of digital

samples of offset seismic data to zero offset, where the NMO-corrected data may not

fall at sampling time, and combining all such NMO-corrected contributions prior to

resampling. This is in contrast to conventional NMO methods wherein an

interpolation is done on the offset trace prior to NMO correction to ensure that the

10   NMO-corrected samples fall on a discrete sampling time. The so-called Random

Sample Interval Imaging (RSI[2)] method of *Wisecup* preserves more high frequency

data than conventional NMO-stack methods. Analogous to and in addition to the loss

of temporal frequencies in conventional processing, there is also a loss of spatial

frequencies in conventional migration and DMO operations. The present invention is

15   a method of preserving these higher temporal and spatial frequencies in partial or full

migration of seismic data using the concepts taught by *Wisecup*.

In one aspect, the present invention is a method for preserving temporal

frequencies in full or partial migration of a line of seismic data using, for example,

DMO. This differs from the method of *Wisecup* in that instead of an NMO operation,

20   data are migrated to discrete sampling locations defined by the source and/or receiver

positions. These locations are commonly midway between sources and receivers.

The migration may be a partial migration such as a DMO, or it may be any full time-

6

or depth-domain migration such as a Kirchoff migration.

In another aspect of the invention, the present invention is a method of preserving temporal and spatial frequencies in full or partial migration of a line of seismic data. This is similar to the preservation of temporal frequencies mentioned

5   above, but additionally, the output spatial locations may be in a location not limited to being midway between a source and receiver location. In yet another aspect of the invention, only higher spatial frequencies are preserved.

Finally, in yet another aspect of the invention, temporal and/or spatial frequencies are preserved during a full or partial 3-D migration of seismic data

10   acquired using a 2-D surface grid or a plurality of 2-D seismic lines wherein the output grid for the migration may be different from the input grid.

The novel features which are believed to be characteristic of the invention, both as to organization and methods of operation, together with the objects and advantages thereof, will be better understood from the following detailed description

15   and the drawings wherein the invention is illustrated by way of example for the purpose of illustration and description only and are not intended as a definition of the limits of the invention:

Figs. 1a, 1b show raypaths, travel times and signals corresponding to a point diffractor at a plurality of coincident source-receiver locations.

20   Fig. 2 illustrates the migration of an input trace to an output location preserving high frequencies.

Fig. 3 illustrates raypaths from a point diffractor located at a position that does not

7

correspond to a surface sampling location.

Fig. 4 shows the results of migration of synthetic data with an input sample interval of 200 ft. to an output sample interval of 5 ft.

Fig. 5 shows the acquisition of a line of marine seismic data for offset source-

5   receiver geometry and illustrate a common offset geometry

Figs. 6A- 6D show the geometry involved in various migration operations.

Fig. 7 illustrates a geometry commonly used in acquiring a 3-D seismic data set.

The first embodiment of the present invention is a modification of the invention disclosed in United States Patent 5,596,546 to *Wisecup* and the contents of

10   which are fully incorporated herein by reference. Referring now to **Figs. 1a and 1b**, a schematic illustration of seismic data acquisition using coincident sources and receivers is shown. The surface of the earth is indicated by **1** and in the subsurface is a point diffractor **5**. The surface locations of the coincident shot-receiver combinations are denoted by **10a, 10b, 10c, ... 10n** and the corresponding raypaths

15   from the surface positions are indicated by **7a, 7b, 7c, ... 7n**. In **Fig. 1a**, the vertical axis is depth and the horizontal axis is the distance relative to the horizontal distance from the point diffractor. For this isolated diffractor in the subsurface, seismic traces that would be recorded at the surface locations are denoted by **18a, 18b, 18c ... 18n** in **Fig. 1b**. In **Fig. 1b**, the vertical axis is time and the horizontal axis is the distance

20   from the point diffractor. The diffraction from the point diffractor are indicated by **19a, 19b, 19c. . .19n** and generally have a time-dependence denoted by the diffraction curve **15**.

8

Denoting by x the horizontal distance between the diffractor and the recording position, the time-distance relation of the diffraction curve for a homogenous medium having a velocity v may generally be given by a relation of the form

$$t_x^2 = t_o^2 + \frac{x^2}{v^2} \qquad\qquad (1)$$

5

Other, more complex relations are possible for inhomogeneous media. The implementation of the first embodiment of the present invention can be better understood by referring to **Fig. 2**. The traces again represent a diffractor such as **5** in Fig. 1a having an acoustic two-way travel time to the zero offset sensor **6** of 1,000

10   milliseconds. In a typical seismic survey, acoustic signals **18a** . . . **18n** at each of the sensors **10a** through **10n** are digitized. During digitization of the signals, individual samples are taken at spaced apart time intervals of the signals generated by each sensor **10a** through **10k**. The samples are generally shown at **26** for the zero-offset sensor **6**, and at **24** for the other sensors. In the example of **Fig. 2** the samples **26, 24**

15   typically are taken at a predetermined time interval of two or four milliseconds, and are taken at substantially coincident times, that is, all the sensors **10a** through **10n** are simultaneously sampled every four milliseconds.

During processing of the digitized signals from the plurality of sensors **10a** through **10n**, an image of the diffractor **5** can be generated by combining the digitized

20   signals from each of the sensors **10a** through **10n** to form a combined output signal. As would be known to those versed in the art, every reflector in the subsurface may

9

be considered to be made up of a multitude of diffractors, and by proper summing

along diffraction curves such as **20**, a coherent image of a reflector may be obtained

as a composite of the image of the multitude of diffractors. The diffraction curve **20** in

Fig. 2 is the same as the curve **15** in Fig. 1a. In order for the combined signal to

5   properly image the diffractor **5**, signal combination must occur so that amplitude

correspondent portions of signals from each of the sensors **10a** through **10n**, such as

the peaks of the wavelets **19a** through **19n**, are combined. In generating the combined

signal, however, amplitude correspondent points, which are shown generally at **28** on

the non-zero offset traces may occur at times other than times at which digital samples

10   are taken, the sample times being shown generally at **24** as previously discussed. In

the present embodiment of the invention, all the digital samples **24** in each of the non-

zero offset traces are time-shifted by a time value which exactly satisfies the

relationship of **eqn. (1)** corresponding to the migration distance (x) for each of the

non- zero offset sensors.

15   The time values for time-shifting each of the non-zero offset traces are

calculated to the degree of precision to which a computer (not shown) which performs

the calculations is capable. The time-shifted samples **24** are stored in a buffer, which

can form part of the computer memory. The combination in the buffer of the samples

26 from the zero-offset trace **18e**, and the time shifted samples **24** from the non-zero

20   offset traces forms a combined signal with constructive interference of the diffraction

signals in a manner similar to that taught in *Wisecup*. The contents of the buffer

typically will contain a total number of samples equal to the product of the number of

sensors multiplied by the number of samples from a single sensor.

The contents of the buffer also can form a stacked single-sensor signal sampled at the equivalent of a much smaller time interval than the predetermined time interval at which the samples 26, 24 were originally taken.

5   The diffraction curve here and the NMO curve given in *Wisecup* are similar. As disclosed in *Wisecup,* the NMO stack obtained therein preserves higher temporal frequencies than prior art methods wherein samples from non-zero offset traces are interpolated prior to being NMO corrected and summed. The increase in higher temporal frequencies in *Wisecup* results from the fact that the average sampling rate

10   can be increased by as much as the multiplicity of traces within the NMO gather and from eliminating the inherent inaccuracy of interpolation.

For identical reasons, the image of the diffraction point (and any seismic image obtained by a process of time or depth migration) using this first embodiment of the invention preserves higher temporal frequency than prior art methods wherein

15   samples for a non-zero migration distance are temporally interpolated prior to being moved along the diffraction curve and summed. As disclosed in *Wisecup,* even if the input data are aliased in time, frequencies above the Nyquist frequency corresponding to the input time-digitization interval are preserved in the output. In an optional embodiment of the present invention, the imaged data are low-pass filtered with a

20   frequency of $M \times f_{Nyq}$ where f_{Nyq} is the input Nyquist frequency and M is an integer less than or equal to N where N is the number of traces in the aperture of the migration operator. M is related to the output sample interval with the output sample

11

interval being as small as 1/N of the input sample interval.

In much of seismic processing and interpretation, obtaining higher spatial resolution is more of a problem than is obtaining higher temporal resolution. Accordingly, in another embodiment of the invention, the migration is performed with

5   only the improved spatial resolution, i.e., the diffraction operator is defined with respect to close spatial locations at discrete sampling values and the contributions from the non-zero offsets are time-interpolated prior to being time shifted. Alternatively, both improved temporal and spatial resolution may be obtained.

The improved spatial sampling is illustrated for an acquisition geometry of

10   depicted in **Fig. 3**. This is similar to **Fig. 1a** in that there is a single diffractor **105** and plurality of coincident source-receiver locations **110a, 110b . . .110i, 110j . . . 110n** with corresponding diffraction raypaths **107a, 107b . . . 107n**. A significant difference is that the surface location **106** corresponding to a zero migration distance does not have an acquisition point located thereat. This is a more realistic model.

15   The discussion above with reference to temporal sampling applies equally to the spatial sample position represented by the point **106**.

Turning now to **Fig. 4**, the results of migrating a set of synthetic data are shown. The data were generated (not shown) for a model with a point diffractor and sampled with a digitization interval of 4 ms. and a spatial sampling of 200 ft. The

20   traces **151a, 151b, 151c...** show the results of migration of the data with the 200 ft. sampling intervals at output positions that differ only by 5 ft.   Loosely applying Rayleigh's criterion (Fundamentals of Optics, Jenkins, F. A., White, H. E., 3rd edition,

12

1957, p300.), a wavelet is assumed to be resolved if the amplitude of the interference

(partially deconstructed energy out of position) is no greater than 81.06 percent of the

true wavelet amplitude. Examination of the plots of the reconstructed events shows

that the amplitude appears to satisfy the Rayleigh criterion within 5 to 10 feet of the

5   correct location, even though the input data was sampled spatially on a 200' grid.

This is verified upon examination of a plot of the peak amplitude (not shown).

Commonly, seismic data are acquired with a plurality of source positions each

of which is recorded at a plurality receiver positions. In such situations, it is common

to use the Dip Moveout (DMO) operation, typically carried out on common offset

10   seismic data as shown in Fig. 5. Shown in the figure is a diffractor 251 and raypaths

from source positions S_1, S_2 to the diffractor 251 and to receiver positions R_1, R_2

corresponding to the source positions, the source-receiver distance being x. The

DMO operation, as described in *Deregowski & Roca*, takes data from a common

offset panel and produces a zero-offset seismic section by summing along a DMO

15   curve that is well defined, just as the migration of a zero-offset section involves

summation along a diffraction curve given by eqn. **(1)**. The DMO operation is well

known and is not discussed hereafter. In one embodiment of the present invention,

data acquired along a seismic line are sorted into common offset panels, each of

which is DMO corrected using the DMO operator and the RSI^2 method disclosed by

20   *Wisecup*. The individual DMO corrected sections may then be stacked.

Alternatively, a prestack or poststack Kirchoff migration may be performed on

one or more lines of seismic data; if poststack migration is used, a DMO may be

13

applied to the prestack data. United States Patent 4,964,103 to *Johnson* discloses a

method in which ray tracing is performed through a 2-D or 3-D model to determine

travel times from any source to any receiver. These travel times may then be used to

perform a Kirchoff migration that basically combines data along diffraction curves

5   determined from the ray-traced travel times.

Next, application of the method of the present invention to 3-D migration is

discussed. Fig. 6a shows a view of a portion of the subsurface with a line 303

indicated thereon. A single diffractor point 301 is shown vertically below a position

307 on line 303. For a coincident shot-receiver geometry, the curve 309 shows a

10   diffraction curve corresponding to the diffractor 301 in the direction of the line 303.

The vertical axis here is shown as time, but it could also be depth. Also shown in Fig.

6a is a diffraction curve 311 for coincident shot-receiver positions along a direction

305 perpendicular to the line 303.

Turning now to Fig. 6b, three diffractors 301, 321 and 341 are shown, with

15   diffractors 321 and 341 being positioned vertically beneath points 327 and 347 on

lines 323, 343 respectively. As in Fig. 6a, diffraction curves 329, 349 for coincident

shot receiver geometry are shown in the inline direction, i.e., along lines 323 and 343

are shown. These diffraction curves 329 and 349 are similar to the curve 309 for the

diffractor 301, and, if the seismic velocities in the subsurface do not change, the

20   curves would be identical. Also shown in Fig. 6b are diffraction curves 330 and 350

for the diffractors 321 and 341 for observation points along line 303.

The diffractions observed along line 303 are shown again in Fig. 6c as curves

14

309, 330 and 350. Next, **Fig. 6d** shows the results of migrating the data of Fig. 6c

using a correct diffraction operator for line 303. The curve 309 is correctly collapsed

to the image point 301' but the diffraction curves 330 and 350 are not correctly

imaged to a single point: instead, a post migration remnant denoted by the curves 321'

5   and 341' are the result of this migration.

The purpose of a 3-D migration of data from a volume of the subsurface is to

properly collapse out-of-plane diffraction curves such as 330 and 350 to a single

point. This may be accomplished by a full 3-D migration, such as that taught by

Johnson.

10   Turning next to the more realistic case of non-zero source receiver offsets, one

embodiment of the present invention is suitable for migration of data acquired in a

grid of 2-D seismic lines such as 305, 325.. 345. The same method may also be used

on a 3-D data set. First a DMO is performed along lines such as 305, 325, 345. This

was discussed above with reference to **Fig. 5b.** Following the DMO, the data are

15   stacked along the lines 305, 325, 345 to simulate zero offset geometry and this is then

followed by a migration of the DMO-stack data. Those versed in the art would

recognize that the same procedure could also be used for data acquired along lines

such as 303, 32, 342.

An example of a commonly used acquisition geometry for 3-D seismic data is

20   shown in **Fig. 7** wherein sources 422 may be placed along seismic lines such as 420a,

420b . . . 420n with receivers 424 deployed along lines 426a, 426b. . .426n. For such

a geometry, full 3-D migration may be used. Alternatively, a method such as that

15

described in United States Patent 4,878,204 to *Black* et al, the contents of which are

fully incorporated herein by reference, may be used to perform a 3-D DMO of the

data. In one embodiment of the present invention, the method of *Black* or other

suitable method, is used to perform a 3-D DMO with enhanced temporal and/or

5   spatial resolution using the methods described above.

In another embodiment of the present invention, a 3-D Kirchoff migration

with enhanced temporal and/or spatial resolution is performed using any suitable

Kirchoff migration method and incorporating the RSI^2 method therein.

While the foregoing disclosure is directed to the preferred embodiments of the

10   invention, various modifications will be apparent to those skilled in the art. It is

intended that all variations within the scope and spirit of the appended claims be

embraced by the foregoing disclosure.

16

CLAIMS

1   1.   A method of preserving spatial frequency components in spatially and

2   temporally sampled signals exceeding a maximum spatial frequency related to

3   a predetermined spatial sample interval, said signals corresponding to a

4   plurality of sensors positioned at spaced apart locations, said method

5   comprising:

6   (a)   for each of said plurality of sensors, generating time adjusted samples

7   at an output location, said adjusted samples generated to provide

8   amplitude correspondence between each of said signals generated by

9   each of said plurality of sensors using a migration operator related to

10   different propagation times of energy to each of said plurality of

11   sensors from associated energy sources; and

12   (b)   combining all of said temporally adjusted samples into a combined

13   output signal having a spatial sampling interval smaller than said

14   predetermined spatial sample interval.

1   2.   The method of claim 1 wherein said migration operator is selected from a

2   group consisting of (i) a post-stack time migration operator, (ii) a post stack depth

3   migration operator, (iii) a pre-stack time migration operator, (iv) a pre-stack depth

4   migration operator, and, (v) a DMO operator.

17

1   3.   The method of claim 1 wherein said sensors and said associated energy

2   sources define one of (i) a single seismic line, (ii) a grid of seismic lines, and, (iii) a 3-

3   D seismic data set.

1   4.   A method of preserving spatial and temporal frequency components in

2   spatially and temporally sampled signals exceeding a maximum spatial frequency and

3   a maximum temporal frequency related to a predetermined spatial sampling interval

4   and a temporal sampling interval, said signals corresponding to a plurality of sensors

5   positioned at spaced apart locations, said method comprising:

6   (a)   for each of said plurality of sensors, generating adjusted samples at an

7   output location, said time adjusted samples generated to provide

8   amplitude correspondence between each of said signals generated by

9   each of said plurality of sensors using a migration operator related to

10   different propagation times of energy to each of said plurality of

11   sensors from associated energy sources; and

12   (b)   combining all of said time adjusted samples into a combined

13   output signal having a spatial sampling time interval smaller than said

14   predetermined spatial sample interval and a temporal sampling interval

15   smaller than said predetermined temporal sampling interval.

18

1 5.   The method of claim 4 wherein said migration operator is selected from a

2 group consisting of (i) a post-stack time migration operator, (ii) a post stack depth

3 migration operator, (iii) a pre-stack time migration operator, (iv) a pre-stack depth

4 migration operator, and, (v) a DMO operator.

1 6.   The method of claim 4 wherein said sensors and said associated energy

2 sources define one of (i) a single seismic line, (ii) a grid of seismic lines, and, (iii) a 3-

3 D seismic data set.

1 7.   A method of preserving at least one frequency component in sampled signals

2 exceeding a maximum frequency related to at least one predetermined sample

3 interval, said signals corresponding to a plurality of sensors positioned at spaced apart

4 locations, said method comprising:

5   (a)   for each of said plurality of sensors, generating adjusted samples at an

6   output location, said adjusted samples generated to provide amplitude

7   correspondence between each of said signals generated by each of said

8   plurality of sensors using a migration operator related to different

9   propagation times of energy to each of said plurality of sensors from

10   associated energy sources; and

19

11   (b)   combining all of said adjusted samples into a combined output signal

12   having a sampling interval smaller than said predetermined sample

13   interval.

1   8.   The method of claim 7 wherein said at least one frequency is selected from the

2   group consisting of (i) a temporal frequency, and, (ii) a spatial frequency.

1   9.   The method of claim 7 wherein said at least one sample interval is selected

2   from the group consisting of (i) a spatial sample interval, and, (ii) a time sample

3   interval.

1   10.   The method of claim 7 wherein said migration operator is selected from a

2   group consisting of (i) a post-stack time migration operator, (ii) a post stack depth

3   migration operator, (iii) a pre-stack time migration operator, (iv) a pre-stack depth

4   migration operator, and, (v) a DMO operator.

1   11.   The method of claim 7 wherein said sensors and said associated energy

2   sources define one of (i) a single seismic line, (ii) a grid of seismic lines, and, (iii) a 3-

3   D seismic data set.

FIG. 1A

Surface Location

FIG. 1B

FIG. 2

FIG. 3

FIG. 5

FIG. 4

FIG. 6A

FIG. 6B

FIG. 6C

FIG. 6D

FIG. 7